

TDS # 25123

1.25 mm Fiber Optic Sleeve Cleaning Swab – Polyester Fiber Tip

PRODUCT DESCRIPTION

The 1.25 mm Fiber Optic Sleeve Cleaning Swab (patent pending) is ideally suited for cleaning contamination from 1.25 mm fiber optic sleeves and polishing pucks. The 1.25 mm diameter polyester tip fits tightly and conforms to the inside of all 1.25 mm mating sleeves, adapters and slurry polishing fixtures. Critical surfaces are cleaned of all contamination. This swab may be used wet or dry to remove dirt and oil contamination. Solvent cleaners such as Electro-Wash® PX or Electro-Wash® CZ cleaner degreasers are 100% compatible with this swab. No adhesives are used in our proprietary manufacturing process, thereby minimizing leachable contaminants. The swab head contains no seams or hard surface that could scratch critical surfaces. Patent Pending.

This product is not designed or intended for cleaning the optical surface of connectors.

TYPICAL APPLICATIONS

Cleaning of fiber optic sleeves 1.25 mm in size.

Removal of slurry from 1.25 mm ferrule polishing fixtures.

COMPATIBILITY

Coventry's Fiber Optic Sleeve Cleaning Swab is compatible with Electro-Wash® PX and Electro-Wash® CZ cleaner degreasers, isopropyl alcohol and acetone.

AVAILABILITY

25123X 1.25 mm head diameter,
17 mm head length
Polypropylene handle
Overall swab length 6 inches
100 / bag, 5 bags per box.

RoHS/WEEE

Status



COVENTRYTM Clean Room Products

Division of Chemtronics

KENNESAW, GA 30152

REV. E (08/13)

Electro-Wash® and Chemtronics® are registered trademarks of Chemtronics. All rights reserved. CoventryTM, is a trademark of Chemtronics. All rights reserved.