

## Electronics

### Tweezers

#### 00 Plastic tips Tweezers




Strong tips

A 5" 130 mm

B 0.04" 1 mm

C 0.08" 2 mm



00CFSA      **Anti-Magnetic Anti-Acid Stainless Steel body with ESD Carbofib (CF) tips**

#### General notes *Plastic Type CF*

- PA66/CF30 polyamide 66 reinforced with 30 wt% carbon fibre
- heat stabilized
- very high rigidity, excellent tensile and flexural strength, fatigue and creep resistance

- low friction, self lubricating properties, excellent wear and abrasion resistance
- good heat capability
- good chemical resistance (oils, grease, fuels, non polar solvents); not resistant to strong acids, alkalis and hot water or steam
- ESD safe material, (avoid powder attraction, sparks generation, ignition sources).
- very low coefficient of linear thermal expansion
- typical applications include handling of sensitive components and devices (electronic components, micro-mechanical parts, glass and ceramic substrates, capillary, etc.)

## Mechanical properties

|                                      |                      |            |
|--------------------------------------|----------------------|------------|
| Flexural modulus +23°C:              | 17000 MPa            | ASTM D 790 |
| Flexural modulus +60°C:              | 12000 MPa            | ASTM D 790 |
| Flexural modulus +90°C:              | 9800 MPa             | ASTM D 790 |
| Flexural modulus +120°C              | 8000 MPa             | ASTM D 790 |
| Tensile strength +23°C               | 210 MPa              | ISO 527    |
| Tensile strength +60°C               | 159 MPa              | ISO 527    |
| Tensile strength +90°C               | 134 MPa              | ISO 527    |
| Tensile strength +120°C              | 117 MPa              | ISO 527    |
| Rockwell hardness M:                 | >100                 | ASTM D 785 |
| Izod-Impact strength (notched) +23°C | 70 J/m               | ASTM D 785 |
| Charpy-Impact strength (unnotched)   | 30 kJ/m <sup>2</sup> | DIN 53453  |

## Thermal properties

|  |             |            |
|--|-------------|------------|
| Temp. of defl. uner load (1.80 MPa):     | 256°C       | ASTM D648  |
| Temp. of defl. uner load (0.45 MPa):     | 260°C       | ASTM D648  |
| Vicat softening temperature (50°C/h 50N) | 254°C       | ISO 306    |
| Coef. of lin.therm expansion, normal:    | 2.80 E-5/°C | ASTM D 696 |
| Continuous Use Temperature               | 130°C       | 20'000 h   |
| Short Time Temperature                   | 190°C       |            |

## Electrical properties

|                             |                     |           |
|-----------------------------|---------------------|-----------|
| Surface resistivity         | 10 <sup>2</sup> Ohm | 100V      |
| Comparative tracking index: | <100 Volts          | IEC 112   |
| Decay time:                 | < 0.1 sec           | 1000-10 V |

## Other properties

|                                      |            |          |
|--------------------------------------|------------|----------|
| Density                              | 1.28 g/ccm | ISO 1183 |
| Water absorption in water 23°C (24h) | 0.60%      | ISo 62   |

## **General Notes Stainless Steel type SA**

- low carbon austenitic steel (Material number 1.4435, DIN X2CrNiMo18-14-3, AISI number 316L)
- contains from 16.5 to 18.5 wt% chromium and has important quantities of nickel and molybdenum as additional alloying elements
- non-magnetizable
- good corrosion resistance to most chemicals, salts and acids
- generally used where corrosion resistance and toughness are primary requirements
- typical applications include tweezers for the electronic industry, watch-makers, jewelers and laboratory and medical applications in moderately aggressive chemical environments

## **Composition**

| Component | Wt.%    | Component | Wt.%      | Component | Wt.%      |
|-----------|---------|-----------|-----------|-----------|-----------|
| C         | ≤0.03   | Si        | ≤1.0      | Mn        | ≤2.0      |
| P         | ≤0.045  | S         | ≤0.03     | Cr        | 17.0-19.0 |
| Mo        | 2.5-3.0 | Ni        | 12.5-15.0 |           |           |

## **Mechanical properties:**

|                            |                       |
|----------------------------|-----------------------|
| State                      | annealed              |
| Density                    | 8.0 g/cm <sup>3</sup> |
| hardness HB30              | ≤215                  |
| Hardness Rockwell B        | 79                    |
| Tensile strength, ultimate | 500-700 MPa           |
| Tensile strength, yield    | 290                   |
| 0.2% Yield stress          | ≤200 MPa              |
| Elongation, break          | 40%                   |
| Modulus of elasticity      | 200 GPa               |

## **Thermal properties**

|                               |              |            |
|-------------------------------|--------------|------------|
| Coef. of lin. therm expansion | 16.0 E-6/°C  | 20°C-100°C |
| Coef. of lin. therm expansion | 17.0 E-6/°C  | 20°C-300°C |
| Specific heat capacity:       | 0.50 J/(g·K) |            |
| Thermal conductivity:         | 15W/(m·K)    |            |
| Continuos use temperature:    | 350°C        |            |
| Max service temperature, ait  | 925°C        |            |

## **Electrical properties**

|             |                 |
|-------------|-----------------|
| Resistivity | 0.75 E-4 Ohm.cm |
|-------------|-----------------|

© IDEAL-TEK SA

Credits